



PROFESSIONAL PERSONAL PROTECTIVE EQUIPMENT

PRODUCT CATALOGUE

A complete range of certified respiratory, head, eye and foot protection engineered for the toughest industrial environments.

What's Inside

01 RESPIRATORY PROTECTION

M-500 Half Mask Respirator	04
G-750 Full Face Gas Mask	05
G-900 Full Face Gas Mask	06
D-100C FFP2 NR D Respirator	07
D-110C FFP3 NR D Respirator	08

02 HEAD PROTECTION

Titanium Shield II – V Vented Helmet	10
Titanium Shield II – NV Non-Vented Helmet	11
W-018V Half Brim Vented Helmet	12

03 EYE PROTECTION

Vision-1000 Safety Goggles	14
Zenith-X Safety Glasses	15
Omni-Seal Safety Glasses	16

04 SAFETY FOOTWEAR

Ironforge S3 SR High Ankle Boot	18
Defender S3 SR Safety Boot	19
IHC-1002 S1P Safety Boot	21

For distributor sales teams: every product page includes certified standards, key features, full technical specifications and recommended applications — everything you need for an on-site customer presentation. Scan the QR code or visit airgearpro.com for full catalogues and video instructions.

SECTION 01

Respiratory Protection

Half masks, full-face gas masks and disposable respirators engineered for reliable protection against dust, fumes, gases and airborne particulates — CE certified for demanding industrial use.

EN
140

EN
136

EN
149

CE
2797



PROFESSIONAL RESPIRATORY PROTECTION

M-500

HALF MASK RESPIRATOR

**ENGINEERED FOR PERFORMANCE.
DESIGNED FOR COMFORT.**

The AirGear Pro M-500 Half Mask Respirator offers reliable respiratory protection with superior comfort, lightweight design and long lasting durability for demanding work environments.

INTRODUCING

ONLY
92g
LIGHTWEIGHT
DESIGN



CE EN140 CERTIFIED

Tested & certified to EN140:1998



DOUBLE BAYONET FILTER CONNECTION

Secure fit for a wide range of filters



LOW BREATHING RESISTANCE

Advanced design for easy breathing



LIGHTWEIGHT ONLY 92g

Designed for comfort during long hours of use



DURABLE & REUSABLE

High quality materials for long term use and easy maintenance



4-POINT ADJUSTABLE HEAD HARNESS

Ensures a secure and comfortable fit

IDEAL FOR USE IN



OIL & GAS



CHEMICAL
INDUSTRY



MANUFACTURING



PAINTING &
SPRAYING



CONSTRUCTION



DUST & INDUSTRIAL
OPERATIONS



TRUSTED & USED IN EUROPEAN, UK & US MARKETS

Quality you can trust.
Protection professionals rely on.



EUROPE



UK



USA



SCAN QR CODE

TO VIEW PRODUCT
CATALOGUE



+971 561977411



sales@airgearpro.com



RELIABLE PROTECTION.
COMFORT YOU CAN TRUST.

INTRODUCING

G-750

FULL FACE GAS MASK

WITH ADVANCED PROTECTION

Engineered for maximum safety, comfort and durability in the most demanding environments.



WIDE 76° FIELD OF VISION

Panoramic, distortion-free view for better visibility and safety.



ANTI-FOG & SCRATCH RESISTANT VISOR

Premium polycarbonate visor for clear vision in all conditions.



FIVE-POINT ADJUSTABLE HEADSTRAP

Provides a secure, comfortable and customized fit.



LIGHTWEIGHT & COMFORTABLE

Ergonomic design with soft face seal for long hours of fatigue-free use.



DURABLE & RELIABLE

Strong ABS body and high-quality materials for long-term performance.



WIDE
76°
FIELD OF
VISION

VOICE DIAPHRAGM

Enhances communication for clear and easy speech during work.

MULTIPLE FILTER PROTECTION OPTIONS



A1P2

Organic gases & vapours
(boiling point > 65°C)
+ particulate protection



AE1-P2

Organic gases & vapours
+ acidic gases & vapours
+ particulate protection



ABEK1-P2

Organic gases & vapours
+ inorganic gases & vapours
+ acidic gases & vapours
+ ammonia & organic amine derivatives
+ particulate protection



SPEECH
DIAPHRAGM



EXHALATION
VALVE

TECHNICAL SPECIFICATIONS

Protection Level	A1P2 (Also available: AE1-P2, ABEK1-P2)
Standard	CE EN136
Connector	Bayonet
Facepiece Material	TPE
Body Material	ABS
Visor Material	Polycarbonate (Anti-fog & Scratch Resistant)
Speech Diaphragm	Yes
Exhalation Valve	Yes
Visual Field	> 76°
Weight	453 g
Storage Life	5 Years

IDEAL FOR USE IN



OIL & GAS



CHEMICAL
INDUSTRY



MANUFACTURING



CONSTRUCTION



PAINTING &
SPRAYING



DUST & INDUSTRIAL
OPERATIONS



TRUSTED & USED IN EUROPEAN, UK & US MARKETS

Quality you can trust.
Protection professionals
rely on.



EUROPE



UK



USA



CE EN136
CERTIFIED



BAYONET
CONNECTION



A1P2
PROTECTION



AE1-P2
PROTECTION



ABEK1-P2
PROTECTION



LIGHTWEIGHT
& COMFORTABLE



DURABLE
ABS BODY



5-POINT
HEADSTRAP



SCAN QR CODE
TO VIEW PRODUCT
CATALOGUE

+971 56 197 7411
sales@airgearpro.com



RELIABLE PROTECTION.
COMFORT YOU CAN TRUST.

AirGear[®] PRO

PROFESSIONAL RESPIRATORY PROTECTION

G-900 FULL FACE GAS MASK

**MAXIMUM PROTECTION.
TOTAL CONFIDENCE.**

Engineered for the harshest environments.
Built for professionals who demand the best.



MAXIMUM PROTECTION

High-efficiency protection against harmful, toxic gases, steam, toxic particles, bacteria, viruses and more.



WIDE VISION

Panoramic anti-fog lens with >92% total vision and >80% binocular vision for superior clarity.



PREMIUM COMFORT

Hypoallergenic silicone mask body with five-point adjustable headband for a secure & comfortable fit.



FLAME RETARDANT

FR-grade hypoallergenic silicone provides flame resistance and skin-safe protection in high-risk environments.



IMPACT RESISTANT

Advanced lens hardening technology offers excellent impact resistance and extended service life.



RD40 CONNECTOR

Designed for single canister use with standard RD40 connector for wide filter compatibility.



TECHNICAL SPECIFICATIONS

	Model Name	G-900		Anti-cyanogen Chloride Time	≥ 30 minutes (30L/min, 1.5mg/L, 80% RH)
	Protection Level	CL2		Oil Mist Penetration Coefficient	≤ 0.005% (30L/min)
	Standard	CE EN 136		Inhalation Resistance	≤ 196 Pa (30L/min)
	Connector	RD40		Exhalation Resistance	≤ 98 Pa
	Material	FR-Grade Hypoallergenic Silicone		Flame Resistance	Meets EN 136 Class 2 requirements
	Lens	Polycarbonate (Anti-fog)		Visual Field	Total > 92% Binocular > 80%
	Headband	Five-point Adjustable		Using Time	Depends on the filter used
	Weight	500g			
	Color	Yellow, Black, Red			
	Storage Life	5 Years			

APPLICATIONS



OIL & GAS



CHEMICAL
PROCESSING



MINING



INDUSTRIAL
MANUFACTURING



POWER GENERATION
& UTILITIES



LABORATORY &
BIOHAZARD RESEARCH



**TRUSTED & USED IN
EUROPEAN,
UK & US MARKETS.**



EUROPE



UK



USA



CALL US
+971 56 197 7411



EMAIL US
sales@airgearpro.com



VISIT OUR WEBSITE
airgearpro.com

PROFESSIONAL RESPIRATORY PROTECTION

D-100C FFP2 NR D RESPIRATOR

FFP2 CE 2797

BREATHE SAFE. WORK CONFIDENTLY.

Advanced protection with comfort and reliability for demanding environments.



HIGH FILTRATION EFFICIENCY

≥94% filtration efficiency against fine particles, dust, smoke & aerosols.



ACTIVATED CARBON LAYER

Helps reduce exposure to nuisance level organic vapors & odors.



COMFORT FIT

Soft inner lining and elastic straps for a secure & comfortable fit.



4-LAYER PROTECTION

Advanced multi-layer construction for superior respiratory safety.



CERTIFIED QUALITY

CE 2797 certified to EN 149:2001+A1:2009 standard.



TECHNICAL SPECIFICATIONS

 Model	D-100C	 Straps	Elastic Headbands
 Standard	EN 149:2001+A1:2009	 Color	Grey
 Certification	CE 2797	 Material	Non-Woven Fabric
 Protection Class	FFP2 NR D	 Protection	Dust, Fumes, Smoke, Mist & Non-Toxic Particles
 Filtration Efficiency	≥94%	 Usage	Single Use (NR)
 Filter Type	Activated Carbon Filter	 Packaging	Individually Packed
 Valve	Exhalation Valve	 Shelf Life	5 Years
 Adjustable Nose Clip	Yes		

IDEAL FOR



CONSTRUCTION



MANUFACTURING



MINING



AGRICULTURE



CHEMICAL PROCESSING



PHARMACEUTICAL

TRUSTED & USED IN

EUROPEAN, UK & US MARKETS.



EUROPE



UK



USA



CALL US

+971 56 197 7411



EMAIL US

sales@airgearpro.com



VISIT OUR WEBSITE

airgearpro.com

PROFESSIONAL RESPIRATORY PROTECTION

D-110C FFP3 NR D

PREMIUM RESPIRATOR

**BREATHE SAFE.
PERFORM CONFIDENTLY.**

Advanced FFP3 protection with superior filtration efficiency for hazardous particles, dust, fumes, smoke & aerosols.



MAXIMUM PROTECTION

High-efficiency protection against dust, fumes, smoke, mist, & non-toxic particles.



≥99% FILTRATION EFFICIENCY

Superior FFP3 filtration efficiency for reliable respiratory safety.



COMFORTABLE FIT

Ergonomic design with adjustable headbands for a secure & comfortable seal.



EXHALATION VALVE

Low breathing resistance with exhalation valve for easy breathing & reduced heat.



CERTIFIED QUALITY

CE 2797 certified to EN 149:2001+A1:2009 FFP3 NR D standard.



TECHNICAL SPECIFICATIONS

	Model	: D-110C		Headbands	: Adjustable Elastic
	Standard	: EN 149:2001+A1:2009		Material	: Non-Woven Fabric
	Certification	: CE 2797		Color	: Grey
	Protection Class	: FFP3 NR D		Protection	: Dust, Fumes, Smoke, Mist & Non-Toxic Particles
	Filtration Efficiency	: ≥99%		Usage	: Single Use (NR)
	Filter Type	: Advanced Meltblown		Packaging	: Individually Packed
	Valve	: Exhalation Valve		Shelf Life	: 5 Years
	Adjustable Nose Clip	: Yes			

IDEAL FOR



CONSTRUCTION



MINING



PHARMACEUTICAL



AGRICULTURE



CHEMICAL
INDUSTRY



MANUFACTURING



LABORATORIES

TRUSTED & USED IN EUROPEAN, UK & US MARKETS.



EUROPE



UK



USA



CALL US

+971 56 197 7411



EMAIL US

sales@airgearpro.com



VISIT OUR WEBSITE

airgearpro.com

SECTION 02

Head Protection

Vented and non-vented industrial safety helmets with integrated retractable visors, engineered for reliable impact protection and all-day comfort on site.

EN
397

ANSI
Z89.1

TYPE I /
TYPE II

SAFETY HELMET

TITANIUM SHIELD II – V

VENTED SAFETY HELMET W/ VISOR

A premium Type I vented safety helmet engineered for dependable top impact protection, an advanced open-vent airflow system, and an integrated retractable polycarbonate visor.

TYPE I TOP IMPACT

CLASS C

410g



1 KEY FEATURES

Vented High-Impact ABS Shell

Openable ventilation system for improved airflow and comfort.

Integrated Retractable Visor

Optical-grade polycarbonate visor, clear or dark lens options.

Six-Point Textile Suspension

Balanced weight distribution with precision ratchet adjustment.

Four-Point Chin Strap

Secure, adjustable fit for demanding work at height.

2 TECHNICAL SPECIFICATIONS

Model Number	W-3000V	Helmet Type	Type I (Top Impact)
Electrical Class	Class C	Shell Material	High-Impact ABS
Suspension	6-Point Textile	Chin Strap	4-Point Adjustable
Ventilation	Adjustable Vented Shell	Visor Material	Polycarbonate
Weight	Approx. 410g	Standard	ANSI Z89.1 / EN 397

3 APPLICATIONS

Construction

Oil & Gas

Manufacturing

Warehousing

Infrastructure

Utilities

Working at Height

SAFETY HELMET

TITANIUM SHIELD II – NV

NON-VENTED SAFETY HELMET W/ VISOR

A premium Type II non-vented safety helmet engineered for superior top and lateral impact protection with certified Class E electrical insulation.

TYPE II TOP & SIDE

CLASS E

510g



1 KEY FEATURES

Non-Vented Sealed ABS Shell

Certified Class E electrical insulation for high-risk environments.

Type II Impact Protection

Protects against both top and lateral impacts.

Integrated Retractable Visor

Optical-grade polycarbonate, clear or dark lens options.

Ergonomic Low-Profile Design

6-point textile suspension & 4-point adjustable chin strap.

2 TECHNICAL SPECIFICATIONS

Model Number	W-3000NV	Helmet Type	Type II (Top & Side)
Electrical Class	Class E	Shell Material	High-Impact ABS
Suspension	6-Point Textile	Chin Strap	4-Point Adjustable
Ventilation	Non-Vented Sealed Shell	Visor Material	Polycarbonate
Weight	Approx. 510g	Standard	ANSI Z89.1 / EN 397

3 APPLICATIONS

Oil & Gas Facilities

Petrochemical Plants

Electrical Contractors

Power Generation

Utilities & Maintenance

Heavy Industrial

SAFETY HELMET

W-018V

HALF BRIM VENTED SAFETY HELMET

Ultralight, highly ventilated helmet with enhanced upward visibility. Hex-flow active ventilation and a 6-point suspension harness for a secure, balanced fit.

PROTECTION CLASS C

330g

4 COLORS



1 KEY FEATURES

Hex-Flow Active Ventilation

Ventilated shell designed for improved airflow and superior comfort.

Advanced 6-Point Suspension

Exceptionally secure and balanced fit on the head.

Easy-to-Use Ratchet Adjustment

Textured adjustment knob for quick, precise sizing.

Ultralight High-Intensity Build

HDPE (or optional ABS) shell — just 330g for minimal neck strain.

2 TECHNICAL SPECIFICATIONS

Model Name	W-018V	Protection Level	Class C (Conductive)
Standard	CE EN 397:2012		ANSI/ISEA Z89.1-2014
Shell Material	HDPE / optional ABS	Suspension	High-Intensity Fiber, 6-Point
Adjustment	Reinforced Ratchet	Weight	330g
Colors Available	Red · Green · Yellow · Blue		

3 APPLICATIONS

Construction

Confined Spaces

General Industrial

Warehousing

SECTION 03

Eye Protection

Safety goggles and glasses with anti-fog, anti-scratch optics and built-in UV filtering — engineered for all-day comfort and maximum visibility on site.

**CE EN 166 /
16321-1**

**ANSI/ISEA
Z87.1**

**CLASS 1
OPTICAL**

SAFETY GOGGLES

VISION-1000

MODEL V-1000

Maximum face coverage, flexible frame and an adjustable secure-fit system. Indirect ventilation controls fogging while a wide-profile seal blocks dust, splashes and impacts.

CLASS 1 OPTICAL

110g

TINTED OPTION



1 KEY FEATURES

Ergonomic Flexibility

Lightweight, flexible PVC frame ensures comfort during extended wear.

Secure Fit System

Fully adjustable headband for a customized, secure fit for all head sizes.

Advanced Fog Control

Indirect ventilation ports allow constant air exchange, preventing fogging.

Comprehensive Seal

Wide-profile design provides superior seal around the orbital area.

2 TECHNICAL SPECIFICATIONS

Model Name	V-1000	Optical Standard	Class 1
Frame Composition	Lightweight, Flexible PVC	Lens Material	High-Impact Polycarbonate
Product Mass	110g	Coatings	Anti-Scratch / Anti-Fog
Standard	CE EN ISO 16321-1:2022, ANSI/ISEA Z87.1-2020		
Customization	Available in Tinted Version		

3 PROTECTS AGAINST

High-Velocity Impacts

Chemical Splashes

UV Radiation

Glare

SAFETY GLASSES

ZENITH-X

MODEL F-3011

Maximum visibility, frameless architecture and superior industrial-grade protection. A lightweight, zero-gravity design for all-day wearability without pressure points.

CLASS 1 OPTICAL

24.5g

4 LENS COLORS



1 KEY FEATURES

Zero-Gravity Comfort

Lightweight construction ensures all-day wearability without fatigue.

Panoramic Vantage

Frameless design removes visual obstructions for high-precision tasks.

Crystal Clarity

Advanced polycarbonate optics for sharp, undistorted vision.

Versatile Utility

Sleek, low-profile fit suited to a wide range of industrial tasks.

2 TECHNICAL SPECIFICATIONS

Model Name	F-3011	Optical Standard	Class 1
Structural Design	Frameless	Lens Material	High-Grade Polycarbonate
Product Mass	24.5g	Coatings	Anti-Scratch / Anti-Fog
Standard	CE EN ISO 16321-1:2022, ANSI/ISEA Z87.1-2020		
Lens Colors	Clear · Smoke · Green · Yellow		

3 PROTECTS AGAINST

High-Velocity Impacts

Chemical Splashes

UV Radiation

Outdoor Glare

SAFETY GLASSES

OMNI-SEAL

MODEL F-3011H

Lightweight glasses comfort with goggle-level dust protection. Specialized inner foam creates a soft barrier that follows facial contours to block wind and dust.

CLASS 1 OPTICAL

34.5g

FOAM SEAL



1 KEY FEATURES

Advanced Sealing

Specialized inner foam blocks wind and dust around the full eye area.

Fatigue-Free Design

Lightweight build allows extended wear through full work shifts.

Ergonomic Grip

Soft rubber temple arms stay secure during high-movement activity.

Multi-Environment Ready

High-performance anti-fog coating handles temperature extremes.

2 TECHNICAL SPECIFICATIONS

Model Name	F-3011H (Omni-Seal)	Optical Standard	Class 1
Core Technology	Inner Foam Lining	Lens Material	High-Impact Polycarbonate
Product Mass	34.5g	Coatings	Anti-Scratch / Anti-Fog
Standard	CE EN ISO 16321-1:2022, ANSI/ISEA Z87.1-2020		
Customization	Available in Smoked Lens		

3 PROTECTS AGAINST

High-Velocity Impacts

Airborne Dust

Chemical Splashes

UV Radiation

Outdoor Glare

SECTION 04

Safety Footwear

Heavy-duty safety boots with composite and steel toe protection, slip resistance and all-day comfort — built for oil & gas, construction and heavy industry.

EN ISO
20345:2022

S1P / S3
SR

EU 35–
48

BUILT TO PROTECT. ENGINEERED TO PERFORM.

IRONFORGE S3 SR

HIGH ANKLE SAFETY BOOT

20CM (8-INCH) | MAXIMUM PROTECTION.
BUILT FOR THE TOUGHEST ENVIRONMENTS.

Engineered with advanced composite technology and premium materials to deliver unmatched safety, comfort and durability in extreme conditions.



COMPOSITE
TOE CAP



KEVLAR®
MIDSOLE



SLIP
RESISTANT



HEAT
RESISTANT



OIL & FUEL
RESISTANT



KEY FEATURES



COMPOSITE TOE CAP

Lightweight, non-metallic protection with 200J impact resistance.



KEVLAR® MIDSOLE

Puncture-resistant (≥1100N) textile midsole for complete underfoot protection.



HEAT RESISTANT OUTSOLE

HRO outsole withstands up to 300°C for 60 seconds.



SLIP RESISTANT (SR)

Superior grip on ceramic tile, steel and greasy surfaces.



OIL & FUEL RESISTANT

Outsole engineered to resist hydrocarbons and industrial oils.



ENERGY ABSORPTION

20 Joules heel energy absorption reduces foot fatigue.

TECHNICAL SPECIFICATIONS

	Height	8-Inch (20 cm)
	Upper	Genuine Full-Grain Leather (WPA)
	Toe Cap	Advanced Composite (200J)
	Midsole	High-Tenacity Kevlar® (Puncture Resistant)
	Outsole	Dual-Density EVA/Rubber
	Lining	Breathable Air Mesh
	Standard	EN ISO 20345:2022
	Safety Rating	S3 SR FO HRO HI CI
	Heat Resistant (Outsole)	Up to 300°C for 60 Sec
	Slip Resistance	SR – Highest Level
	Fuel & Oil Resistance	Yes
	Water Resistance	WPA – Water Penetration & Absorption Resistant
	Sizes	EU 35 – 48

BUILT FOR EXTREME INDUSTRIES



OIL & GAS



CONSTRUCTION



MINING



MANUFACTURING



WAREHOUSING



HEAVY INDUSTRY



LOGISTICS



**TOUGH ON
HAZARDS.
COMFORTABLE
EVERY STEP.**

ADVANCED PROTECTION. UNCOMPROMISED COMFORT.



ANTI-STATIC
Protection against
electrostatic
discharge.



**BREATHABLE
LINING**
Keeps feet dry
and comfortable.



ANKLE SUPPORT
High ankle design
for maximum
stability.



DURABLE DESIGN
Reinforced stitching
and high-tensile
lacing system.



ALL-DAY COMFORT
Ergonomic fit for
long hours on
the job.

TRUSTED & USED IN
EUROPEAN, UK & US MARKETS.



EUROPE



UK



USA



+971 56 197 7411



sales@airgearpro.com



airgearpro.com

EN ISO 20345:2022

S3 SR CERTIFIED

SRA + SRB SLIP RATED

— SAFETY FOOTWEAR

DEFENDER

S3 SR SAFETY BOOT

WATERPROOFED.
REINFORCED. RELENTLESS.

Steel protection, superior slip resistance, antistatic performance and water resistance — engineered for oil & gas, construction and the harshest heavy-duty industrial applications.

• 200J TOE IMPACT

• SRA+SRB SLIP RATED

• WATER-RESISTANT



01 KEY PROTECTIVE FEATURES



STEEL TOE PROTECTION

200-Joule impact and compression resistant steel toe cap safeguards against heavy falling objects.



PUNCTURE-RESISTANT MIDSOLE

Steel midsole plate rated ≥ 1100 N shields the foot from sharp debris on site.



DUAL SLIP RESISTANCE

SRA + SRB (SR certified) delivers excellent grip on both ceramic and steel surfaces.



WATER-RESISTANT UPPER

Water-resistant cow split leather keeps feet dry and protected in wet working conditions.



ANTISTATIC CONSTRUCTION

0.1–1000 MΩ antistatic properties reduce the risk of static discharge in sensitive environments.



ENERGY-ABSORBING HEEL

≥20 Joule heel absorption cushions every step through long, demanding shifts.



FUEL & OIL RESISTANT OUTSOLE

Dual-density PU outsole resists fuel, oil and slips in wet, contaminated conditions.



BUILT FOR HARSH ENVIRONMENTS

Breathable air mesh lining supports long working hours in the toughest job sites.

02 TECHNICAL SPECIFICATIONS

FULL SPEC SHEET

Model Name	DEFENDER S3 SR	Protection Level	S3 SR
Standard	EN ISO 20345:2022	Upper Material	Water-Resistant Leather
Lining	Breathable Air Mesh	Toe Cap	Steel, 200J Impact
Midsole	Steel, ≥1100 N	Outsole	Dual-Density PU
Slip Resistance	SRA + SRB	Antistatic	0.1–1000 MΩ
Heel Energy Absorption	≥ 20 Joules	Sizes Available	EU 35 – 48

03 RECOMMENDED APPLICATIONS



Oil & Gas



Construction & Infrastructure



Manufacturing & Engineering



Warehousing & Logistics



Utilities & Maintenance

Engineered for the Extremes

Independently rated S3 SR: steel toe and midsole protection, dual-certified slip resistance, antistatic performance and water-resistant construction.



ISO 20345



PROTECTION



WATER-RES.



MARKED



CALL US
+971 56 197 7411



EMAIL US
sales@airgearpro.com



VISIT US
airgearpro.com

EN ISO 20345:2022
CERTIFIED S1P

— SAFETY FOOTWEAR

IHC-1002

S1P SAFETY BOOT

**BUILT TO LAST.
ENGINEERED TO PROTECT.**

Durable, comprehensive foot protection with steel-toe reinforcement and a puncture-resistant midsole, wrapped in lightweight materials for all-day comfort on the toughest job sites.

• 200J TOE IMPACT

• $\geq 1100\text{N}$ MIDSOLE

• $\geq 20\text{J}$ HEEL ENERGY



01 KEY PROTECTIVE FEATURES



STEEL TOE PROTECTION

200-Joule impact and compression resistant steel toe cap safeguards against heavy falling objects.



PUNCTURE-RESISTANT MIDSOLE

Steel midsole plate rated $\geq 1100\text{ N}$ shields the foot from sharp debris on site.



ANTISTATIC CONSTRUCTION

0.1–1000 M Ω antistatic properties reduce the risk of static discharge in sensitive environments.



ENERGY-ABSORBING HEEL

≥ 20 Joule heel absorption cushions every step through long, demanding shifts.



FUEL & OIL RESISTANT OUTSOLE

Dual-density PU outsole resists fuel, oil and slips (SRA rated) in wet, contaminated conditions.



BUILT FOR HARSH ENVIRONMENTS

Cow split leather upper with breathable air mesh lining for long working hours in demanding sites.

02 TECHNICAL SPECIFICATIONS

FULL SPEC SHEET

MODEL NAME

IHC-1002

PROTECTION LEVEL

S1P

STANDARD

EN ISO 20345:2022

UPPER MATERIAL

Cow Split Leather

LINING

Breathable Air Mesh

TOE CAP

Steel, 200J Impact

MIDSOLE

Steel, ≥ 1100 N

OUTSOLE

Dual-Density PU

SLIP RESISTANCE

SRA

ANTISTATIC

0.1-1000 M Ω

HEEL ENERGY ABSORPTION

≥ 20 Joules

SIZES AVAILABLE

EU 35 - 48

03 RECOMMENDED APPLICATIONS



Oil & Gas



Construction & Infrastructure



Manufacturing & Engineering



Warehousing & Logistics



Utilities & Maintenance

Certified Quality You Can Stand On

Independently rated S1P for toe protection, puncture resistance, antistatic performance and heel energy absorption.



ISO 20345



PROTECTION



MARKED



CALL US
+971 56 197 7411



EMAIL US
sales@airgearpro.com



VISIT US
airgearpro.com



Reliable Protection. Comfort You Can Trust.

AirGearPro equipment is trusted and used by protection professionals across European, UK and US markets — now available to distributors and customers in the UAE.

CALL

+971 56 197 7411

EMAIL

sales@airgearpro.com

WEB

airgearpro.com

Europe | UK | USA | UAE

This catalogue is intended for distributor sales use. Product specifications subject to change — please confirm certification documents and current pricing with your AirGearPro account manager before final customer commitment.